

NOTES:



SAWCUT CONTROL JOINTS MAY BE PERMITTED IN STREETSCAPE AREAS IF APPROVED BY THE PROJECT ARCHITECT/ENGINEER AND THE CITY ENGINEER PRIOR TO BID AND CONSTRUCTION.

CONCRETE WALK TO BE CLASS "C" ODOT 499 NO. 57 OR 67 LIMESTONE (SEE BELOW) NO EXPANSION JOINTS ARE TO BE PLACED AGAINST BRICK PAVER SECTIONS





EXPANSION JOINT — 1/2" CLOSED CELL EXPANSION JOINT FILLER TO BE SEALTIGHT CERAMAR WITH 1/2" PEEL STRIP OR EQUAL. PLACE EXP. JOINTS AGAINST BUILDINGS, STRUCTURAL FOUNDATIONS, AND 60FT O.C. IN WALK, TYP. SEAL EXPANSION JOINTS WITH POLYURETHANE ELASTOMERIC SEALANT TREMCO THC 900/901 OR EQUAL.

TYPICAL TOOLED AND CUT CONTROL JOINT, 1/4 DEPTH OF SLAB

5" PLAIN PORTLAND CEMENT CONCRETE PAVEMENT, ODOT ITEM 608 AND 499, AS PER PLAN.

4" COMPACTED THICKNESS AGGREGATE BASE COURSE, ODOT ITEM #304.

ODOT REFERENCES ARE FROM THE CURRENT ODOT CONSTRUCTION AND MATERIAL SPECIFICATIONS. ANY DISCREPANCIES SHALL BE SUBJECT TO THE CITY ENGINEER'S DISCRETION.

ALL CONCRETE CONSTRUCTION TO CONFORM TO CURRENT CITY OF CANTON SPECIFICATIONS FOR CONSTRUCTION, REPAIR AND REPLACEMENT OF SIDEWALKS, CURBS AND DRIVEWAYS.

NOTE: NO FOUNDRY SAND OR SLAG IS PERMITTED IN AGGREGATE BASE (304).

AGGREGATE IN SURFACE CONCRETE SHALL BE AASHTO M NO. 57 OR 67 LIMESTONE ONLY.

ALL CONCRETE FOR CURB AND WALKS SHALL BE ODOT 499, CLASS C.

CLASS C OPTION 1 MAY BE USED BETWEEN MAY 1 AND OCTOBER 15.

AGGREGATE IN SURFACE CONCRETE SHALL BE NO. 57 OR 67 LIMESTONE ONLY.

OFFICE OF THE CITY ENGINEER

CANTON, OHIO

DANIEL J. MOEGLIN, P.E., CITY ENGINEER

2436 30th St. NE 44705

330-489-3381

APPROVED DATE: FEB. 2012

OHIO

APPROVED BY: JTD

E., CITY ENGINEER
DRAWING FILE NAME:
ce\_40-47\_STREETSCAPE.dwg

REVISED JOINT NOTES

DATE 2/26/2019

DESCRIPTION

REVISIONS

STANDARD DRAWING NO. 42

STREETSCAPE CONCRETE
WALK PAVEMENT DETAILS

SHEET 1 OF 1